

Gips-Fix Metal L /XL



Material thickness

Type L up to 12 mm

Type XL up to 24 mm


Screws Ø

Type L 3,5 - 4,5 mm

Type XL 4,0 - 5,0 mm


Material

Steel, galvanised



Application Gips-Fix Metal L

No pre-drilling required, the dowel can be directly hammered in.
The dowel spreads when screwing in, which offers a secure hold.



Application Gips-Fix Metal XL

For wall thicknesses up to 24 mm.
Same function as Gips-Fix L.

Gips-Fix Metal L (MZ026)

Type	Dimension	Dowel Ø mm	Dowel length mm	Contents PU Pcs.	Weight KG/PU	Shipping box PU	Item No.
MZ026 L	12	12,00	30,00	100	0,19	70	970 18 2

Gips-Fix Metal XL (MZ028)

Type	Dimension	Dowel Ø mm	Dowel length mm	Contents PU Pcs.	Weight KG/PU	Shipping box PU	Item No.
MZ028 XL	24	16,00	43,00	100	0,50	12	970 18 4

Don Quichotte B.V.

P.O. Box 60, 5700 AB Helmond
Industrial Zone 9081
Gerstdijk 17, 5704 RG Helmond
The Netherlands

Tel.: +31 492 74 50 00
Fax: +31 492 74 50 99
info@don-quichotte.com
www.don-quichotte.com