

## Cable tie, standard, natural (OZ090)



The addition of carbon, means that it is UV-resistant according to EN ISO 4890, corresponds to approx. 3 years of sunlight, with plastic tongue/tab, according to DIN EN 62275 VDE 0604-201:2010-07

UL approval 94, Class V2

Use temperature -40 °C to 85 °C, mounting temperature -10 °C to 60 °C

Melting point at 256 °C

Oxygen index [LOI]: 27%, moisture intake 2.7% at 50% relative humidity



### Master data

Item number	905612
Type	OZ090 2,5x150
Description 1	Cable ties
Description 2	natural
Brand	DQ
Dimension	2,5x150
Colour	Natural
Material	Polyamide
PU1	100
Unit of quantity	Piece
Weight	0.044 kg
Weight unit	kg/100 pc.

### Dimensions

Length	150 mm
Width	2.5 mm
Height	1 mm

## Cable tie, standard, natural (OZ090)

### Technical data

Version for	Externally toothed
Fastening type	Without
Labelling area	Without
For pipe diameter, max.	35 mm
Halogen-free	yes
Releasable lock	no
Max. Bundle diameter	35 mm
minimum breaking load	80 kN
Reflective	no
Permitted temperature range, max.	85 °C
Permitted temperature range, min.	-40 °C
Transparent	no
UV-resistant	no