

Cable tie, standard, natural (OZ090)

The addition of carbon, means that it is UV-resistant according to EN ISO 4890, corresponds to approx. 3 years of sunlight, with plastic tongue/tab, according to DIN EN 62275 VDE 0604-201:2010-07

UL approval 94, Class V2

Use temperature -40 °C to 85 °C, mounting temperature -10 °C to 60 °C

Melting point at 256 °C

Oxygen index [LOI]: 27%, moisture intake 2.7% at 50% relative humidity



Master data

Item number	905620
Type	OZ090 4,8x203
Description 1	Cable ties
Description 2	natural
Brand	DQ
Dimension	4,8x203
Colour	Natural
Material	Polyamide
PU1	100
Unit of quantity	Piece
Weight	0.133 kg
Weight unit	kg/100 pc.

Dimensions

Length	203 mm
Width	4.8 mm
Height	1.6 mm

Cable tie, standard, natural (OZ090)

Technical data

Version for	Externally toothed
Fastening type	Without
Labelling area	Without
For pipe diameter, max.	47 mm
Halogen-free	yes
Releasable lock	no
Max. Bundle diameter	47 mm
minimum breaking load	220 kN
Reflective	no
Permitted temperature range, max.	85 °C
Permitted temperature range, min.	-40 °C
Transparent	no
UV-resistant	no