

Cable tie, standard, UV-resistant, black (OZ090)

The addition of carbon, means that it is UV-resistant according to EN ISO 4890, corresponds to approx. 3 years of sunlight, with plastic tongue/tab, according to DIN EN 62275 VDE 0604-201:2010-07

UL approval 94, Class V2

Use temperature -40 °C to 85 °C, mounting temperature -10 °C to 60 °C

Melting point at 256 °C

Oxygen index [LOI]: 27%, moisture intake 2.7% at 50% relative humidity



Master data

Item number	905644
Type	OZ090 7,6x300
Description 1	Cable ties
Description 2	black
Brand	DQ
Dimension	7,6x300
Colour	Black
Material	Polyamide
PU1	100
Unit of quantity	Piece
Weight	0.417 kg
Weight unit	kg/100 pc.

Dimensions

Length	301 mm
Width	7.6 mm
Height	1.8 mm

Cable tie, standard, UV-resistant, black (OZ090)

Technical data

Version for	Externally toothed
Fastening type	Without
Labelling area	Without
For pipe diameter, max.	73 mm
Halogen-free	yes
Releasable lock	no
Max. Bundle diameter	73 mm
minimum breaking load	530 kN
Reflective	no
Permitted temperature range, max.	85 °C
Permitted temperature range, min.	-40 °C
Transparent	no
UV-resistant	yes