

Speedplug SP, flat collar, cylinder head (SP001)

To fix wall signs, cable conduits, steel, aluminium or plastic sheets.



Master data

| | |
|------------------|----------------------------|
| Item number | 999402 |
| Type | SP001 SPTB 6x40 |
| Description 1 | Nail plug |
| Brand | DQ |
| Dimension | Ø6xL40mm |
| Colour | Natural |
| Material | Steel |
| Surface | Electrogalvanized |
| Surface standard | EN ISO 19598 / EN ISO 4042 |
| PU1 | 200 |
| Unit of quantity | Piece |
| Weight | 0.419 kg |
| Weight unit | kg/100 pc. |

Dimensions

| | |
|--------|-------|
| Length | 42 mm |
|--------|-------|

Technical data

| | |
|---------------------------|------------------|
| Pull-out force | 1800 N |
| Drill hole depth | 41 mm |
| Drill hole diameter, min. | 6 mm |
| Thread | M6 |
| Thread metric | 6 |
| Halogen-free | yes |
| Head diameter | 8 mm |
| Head shape | Countersunk head |
| With edge | yes |
| With bolts | yes |
| Nail diameter | 3.8 mm |
| Nail length | 42 mm |
| Shank diameter | 3.8 mm |
| Screw system | Pozidrive PZ |
| Pin shape | Nail screw |

The worker's choice



Speedplug SP, flat collar, cylinder head (SP001)