

Speedplug SP, flat collar, cylinder head (SP001)

Nail plug for electrical engineers, sanitary installation engineers, drywall builders and roofers. Pre-assembled for the fixing of clips, profiles or slats on concrete stone or masonry.



Master data

| | |
|------------------|----------------------------|
| Item number | 999100 |
| Type | SP001 SP 5x35 |
| Description 1 | Nail plug |
| Brand | DQ |
| Dimension | Ø5xL35mm |
| Colour | Natural |
| Material | Steel |
| Surface | Electrogalvanized |
| Surface standard | EN ISO 19598 / EN ISO 4042 |
| PU1 | 200 |
| Unit of quantity | Piece |
| Weight | 0.292 kg |
| Weight unit | kg/100 pc. |

Dimensions

| | |
|--------|-------|
| Length | 38 mm |
|--------|-------|

Technical data

| | |
|---------------------------|------------------|
| Pull-out force | 1300 N |
| Drill hole depth | 36 mm |
| Drill hole diameter, min. | 5 mm |
| Thread | M5 |
| Thread metric | 5 |
| Halogen-free | yes |
| Head diameter | 7.7 mm |
| Head shape | Countersunk head |
| With edge | yes |
| With bolts | yes |
| Nail diameter | 3.5 mm |
| Nail length | 38 mm |
| Shank diameter | 3.5 mm |
| Screw system | Pozidrive PZ |
| Pin shape | Nail screw |

Speedplug SP, flat collar, cylinder head (SP001)