

## Speedplug SP, flat collar, cylinder head in bucket (SP001/SP014)

Nail plug for electrical engineers, sanitary installation engineers, drywall builders and roofers. Pre-assembled for the fixing of clips, profiles or slats on concrete, stone or masonry.



### Master data

Item number	951019
Type	SP014 SPKK 5x45
Description 1	Nail plug
Brand	DQ
Dimension	Ø5xL45mm
Colour	Natural
Material	Steel
Surface	Electrogalvanized
Surface standard	EN ISO 19598 / EN ISO 4042
PU1	200
Unit of quantity	Piece
Weight	0.365 kg
Weight unit	kg/100 pc.

### Dimensions

Length	48 mm
--------	-------

### Technical data

Pull-out force	1300 N
Drill hole depth	46 mm
Drill hole diameter, min.	5 mm
Thread	M5
Thread metric	5
Halogen-free	yes
Head diameter	7.7 mm
Head shape	Countersunk head
With edge	yes
With bolts	yes
Nail diameter	3.5 mm
Nail length	48 mm
Shank diameter	3.5 mm
Screw system	Pozidrive PZ
Pin shape	Nail screw

# Speedplug SP, flat collar, cylinder head in bucket (SP001/SP014)

The worker's choice

